Certificate of Location of Government Corner

ID#: 652104 **Description:** 1/4 SEC COR 21 28 65 **Date Set:** 4/28/1992 **County:** Olmsted

Section: 21 **Township:** 106N **Range:** 15W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 1' east of fence south, 1 1/2' north E-W fence and 1 1/2' north of CP
Post w/sign 1' north
This corner is located by GPS measurement

Corner History:

6-1854 Michael Karrick 40.00 set quarter section post in mound with trench pits, charred stake, and Osage Orange seeds NE & SW.

3-1895 W.Fraser (P.618 No.561) found mound with old stake in center just North of corner post set square boulder in place of old stake with new stake by side. 1/16 North set stake and boulder M&L 19.97 (1318.02).

6-1905 W.Fraser (P.92B) found stone set p.618. Meas West 40.02 to stone set this survey

5-28-1928 J.Kerr (B.2 1928) P.38 random line N-S 1/4 line 30' W of N 1/4 28 (not described) line fell 20' W of S 1/4 (not described). Set center 28 8 x 10 x 26 at true inters lines 2645.63 from E 1/4 28.

6-16-1972 County Surveyor found 1/16 stone and stake North, dug and probed entire area around corner post of fences E-W-N for W.Fraser's stone, found small dark spot North of corner post set 3/8" ele fence post there.

4-28-1992 County Surveyor set cast iron cap on telspar pipe at 3/8" iron position set in (1972) where Co. Surveyor found mark.

3-8-2000 County Surveyor found cast iron cap on telspar pipe in good condition.