Certificate of Location of Government Corner

ID#: 652105 **Description:** SEC COR 20 21 28 29 65 **Date Set:** 6/29/1972 **County:** Olmsted

Section: 21 **Township:** 106N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of CR 150
Center of No. plate in E side PP #40226 SW 71.05'
SE corner of house (slope meas) NW 83.7'
Center 14" cedar tree (slope meas.) NW 100.5'
Center of No. Plate PP #7637 NE 107.97'
This corner is located by GPS measurement

Corner History:

6-1854 Michael Karrick 40.50 creek 4 lks wide runs NE and leave Asspen thicket bears NW. 80.00 set post for corner to sections 20,21,28 and 29 erected mound with trench pits, charred stake and Osage Orange seeds at each angle.

6-1905 W. Fraser (P.92B) Corner gone replaced with stone as corner. Meas SW 20 (stone set B trees) to 1/4 21-28 (stone found) set corner 40.02 1/3 dist. 2641.32. Meas 1/4 20-21 (stone found) to SW cor 28 (stake set from BT) set corner 39.84 1/3 dist. 2629.44. 1/16 North set stake M&L 19.92 1314.72.

7-1911 C. Larson (Bk.B P.160) found the stone.

4-1933 J. Kerr (Bk.8 P.63) found the stone and set an iron beside it.

4-1953 county highway department assumed corner, set a 8"x8"x30" conc. monu.

6-29-1972 County Surveyor found the recorded stone and the Co. conc. monu., reset conc. monument 5' down with CIM on top.

Note: The correct corner was .3' E and 3.3' S of the Co. conc. monu.

4-10-2002 County Surveyor found CIM down 0.9' in good condition.