Certificate of Location of Government Corner

ID#: 652106 **Description:** 1/4 SEC COR 20 21 65 **Date Set:** 12/13/2011 **County:** Olmsted

Section: 21 **Township:** 106N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is down 0.8'
The corner falls in centerline of twp road east and 7' west of centerline of CR 150
Ground wire on S side PP #40217 NNW 29.25'
Conc. nail in NE side PP #7656 SE 61.72'
Center top of a metal tele. box NW 48.59'
This corner is located by GPS measurement

Corner History:

6-1854 Michael Karrick 40.00 set quarter section post. White Oak 6 S 38 E 33. Dug trench. 68.40 creek 20 lks wide runs NE.

1-1891 T. Fraser (Bk. A P.449) found the stake in center of mound reset cor.

3-1895 W. Fraser (Bk. A P.618) found corner and set 1/16 stone and stake East.

7-1911 C. Larson (Bk B P.160) found boulder.

1933 J. Kerr found boulder.

7-1953 county highway department set an 8" by 8" by 30" conc. monu. at assumed location.

6-19-1972 County Surveyor found the county concrete monument and the recorded boulder. Set a C.I.M. over the stone and a 1" by 4' iron.

Note: This is a correction of a corner. The correct boulder was 8.0' West and 1.0' South of the county concrete monument at their assumed location.

4-10-2002 County Surveyor found CIM w/head broken down 0.9'.

8-4-2008 V. Fangman found monument with broken head.

12-13-2011 County survey crew found CIM with broken top. Removed and replaced with a new CIM.