Certificate of Location of Government Corner

ID#: 652305 **Description:** SEC COR 22 23 26 27 65 **Date Set:** 4/29/1968 **County:** Olmsted

Section: 23 **Township:** 106N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 2' east of N-S fence and 5' south of fence west
Center 20" Elm NE 130.8'
This corner is located by GPS measurement

Corner History:

6-1854 Michael Karrick 80.00 set post for corner to sections 22,23,26 and 27, erected mound with trench pits, charred stake and Osage Orange seeds at each angle.

3-1878 Hunter (P.331 No.325) found original stake in mound by fence with pits plain. 1/16 West set temp stake 19.99-1/2 M&L N89° 25 W. 1/16 South set oak stake 20.04-1/2 M&L to stake in center road.(replaced this stake with 4 x 6 x 15 well down and 7 x 10 x 18 on top N 1° E.) 1/16 center NE 1/4 27 set stake inters lines (parties to set stone later).

6-1887 Hunter (P.420 No.409) did not use this corner in this survey but Will Fraser caption below it.

11-1893 W.Fraser found stake (P.455) also tested by line from South over 1/16 stake set boulder ane stake not marked as section corner. 1/16 East planted boulder stone M&L 19.93-1/2, staked line South of 1/16. Meas South 39.95 to stone placed (P.331)

9-1891 Thos. Fraser (P.455 No.439) found marked stake 4' East corner fence post, left as is. 1/16 North found old stake after running line exactly M&L 19.92-1/4 set stone 6 x 8 x 20. 4" Burr Oak N 22-1/2 E 23 lks. (1314.88)

12-1894 W.Fraser (P.562 No.516) found boulder place. 1/16 North found stone (P.455). 1/16 East found stone caption P.420 M&L 19.93-1/2. 1/16 center SW 1/4 23 set stone and stake M&L 19.94-1/2 N-S 1/16 line.

4-29-1968 J.Kerr corner set, found stone set CIM and 1/2 of CIM base by old stone.

8-20-1973 County Surveyor CIM in precarious position, being 2' east of fence not in corner so modern plows could easily hook CIM which is only 4 or 5 inches deep.

3-8-2000 County Surveyor found CIM down 0.6' in good condition.