Certificate of Location of Government Corner

ID#: 652404 **Description:** 1/4 SEC COR 24 25 65 **Date Set:** 7/23/93 **County:** Olmsted

Section: 24 **Township:** 106N **Range:** 15W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

Post w/sign 1' east
This corner is located by GPS reference stations "Swede A & B"

Corner History:

6-1854 Michael Karrick 37.60 creek 30 lks wide runs NE random line. 40.00 set quarter section post true line. Ash 8 S 35 E 20. Ash 12 N 15 E 11. 40.60 same creek 30 lks runs South random line. 41.20 same creek runs NE random line.

5-1872 T. Hunter (P.200 No.209) corner gone, reset by 1 BT standing and stump of another set stake East to fence by.

5-1873 T. Hunter (P.222 No.225) found stake standing set (P.200). 1/16 South set stake M&L 19.96 1317.36.

4-1898 W.Fraser (P.624 No.566) found stake remains, tested SE bearing tree and stump NE BT . Set stone 2 x 12 x 20 and new BT 8" ash S 29° W 14 lks. 1/16 North set stake M&L 19.97. 1/16 West set stake and stone M&L 19.98. 1/16 cente4r SW 1/4 24 set stake M&L 19.98-1/2 on E-W 1/16 line.

8-1959 J. Kerr stone 2" x 10" found by McGhie references. 2636' West to fence running N. Spike in 12" tree NNE 15.0 at SW 24 where rod set in line fence North and 3' N of center road. Bent 60d in 20" turn tree West 13.4.

6-23-1972 County Surveyor found limestone with iron on West side in flood plane area in slight depression. Left as found. Meas and run line West to stone found at 23-24-25-26. Took new bearing tree near where missing tree gone (lying on ground) 20d in 8" bass wood tree SW 12' no 1/16 West in open cult field.

7-22-1993 County Surveyor found stone with 1/2" iron on West side set post and sign ± 1' East of corner.

7-23-1993 County Surveyor stone found is 2" x 0/16" x 21" triangle shaped point up. Set cast iron cap on telspar pipe on square pipe at stone location (W.F. stone 2 x 12 x 20 he used average width).

10-20-2006 County Surveyor found cast iron cap on telspar pipe up 0.3' in good condition.