Certificate of Location of Government Corner

ID#: 652406 **Description:** 1/4 SEC COR 23 24 65 **Date Set:** 8/17/1973 **County:** Olmsted

Section: 24 **Township:** 106N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 1' south of E-W fence, 1' east of fence south and 1 1/2' SE of CP
Nail in N side 12" Cherry W 1.7'
Post w/sign 2' south
This corner is located by GPS reference stations "Koskovich A & B"

Corner History:

1854 Gov't Notes M.G. Karrick, Deputy Surveyor North between sections 23 and 24. 40.00 chs. Set quarter sections 23 and 24. Burr Olk 10 in. S25°W 180 lks. Blk. Oak 11 in. S25°E 23 lks.

6-1874 Thomas Hunter (P.254 No.2540, County Surveyor, found original stake standing.

6-1874 T. Hunter (P.225 No.225) found stake.

12-1894 William Fraser, County Surveyor, found stake and set a limestone by its side.

4-1898 W. Fraser (P.624 No.556) found stone.

8-17-1973 County Surveyor found a limestone 2"x6"x10'. Set a C.I.M. over stone and glass.

7-26-1993 County Surveyor found CIM in good condition 18" NW of 12" diameter Cherry tree. Cor is ± 18" SE of S-E-W fence line corner post.

10-10-2006 County Surveyor found CIM down 0.2' in good condition.