Certificate of Location of Government Corner

ID#: 652409 **Description:** SEC CEN 24 65 **Date Set:** 8/9/2001 **County:** Olmsted

Section: 24 **Township:** 106N **Range:** 15W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

1/2" pipe w/cap RLS #14888

Reference Ties:

The corner falls 1-1/2' north of east-west fence, in line with fence south, and 1-1/2' north of corner post
The monument is at the surface
This corner is located by GPS reference stations "Donovan E & F"

Corner History:

5-14-1872 Thomas Hunter, County Surveyor, (Book A, Page 200, Survey No.209) set stake on north-south quarter line at 39.52 chains (2608.32') north of South 1/4 at end of fence east.

6-19-1874 Thomas Hunter, County Surveyor, (Book A, Page 255, Survey No. 255) set temporary stake at intersecting quarter lines. The corner falls 31-1/2 links (20.79') north of north side of end post of fence east. 1/16th North set stake midway and on line at 20.00 chains (1320.00') to North 1/4. RPs - 8" Bur Oak S30-1/2°E 53 links (34.98'), 8" Bur Oak S51°W 33 links (21.78'). 1/16th West set stake midway and on line at 20.05 chains (1323.30') to West 1/4. 1/16th Center of NW 1/4 set stake midway and on line at 19.93 chains (1315.38') on east-west sixteenth line.

4-12-1898 William Fraser, County Surveyor, (Book A, Page 624, Survey No. 566) set stake and boulder stone at intersecting quarter lines. 1/16th North found SE witness tree and stump of SW witness tree. Set stake with orginial stake. 1/16th South set stake midway and on line at 19.97 chains (1318.02') to South 1/4. 1/16th Center of SW 1/4 set stake midway and on line at 19.98-1/2 chains (1319.01') on east-west sixteenth line.

4-21-1981 Thomas Taylor used computed center at intersecting quarter lines.

3-15-1994 Ed Kuisle, County Surveyor, used computed center at intersecting quarter lines for Olmsted County Highway Right of Way Plats No. 96 & 97.

5-24-2001 McGhie & Betts, Inc. used computed center at intersecting quarter lines.

8-9-2001 Vince Fangman set 1/2" pipe w/cap RLS #14888 at interesting quarter lines.

10-20-2006 County Survey Crew found 1/2" pipe w/cap RLS #14888 at surface in good condition and measured its position using GPS.

5-1-2012 Joel Thoreson, County Surveyor, recommends using the computed intersection of quarter lines for the center of section. Based on the county's section breakdown, the 1/2" pipe w/cap, as located by GPS in 2006, falls 0.01' south and 0.03' east of the computed center.