Certificate of Location of Government Corner

ID#: 652605 **Description:** SEC COR 26 27 34 35 65 **Date Set:** 10/28/1970 **County:** Olmsted

Section: 26 **Township:** 106N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 2' west of fence north, 1' south of centerline of E-W twp road and 9' west of centerline of twp road south
Bottle cap in SE side PP #7466 SW 47.4'
Top center of telephone cable box (metal box) ESE 99.55'
Punch cross in E end 24" CMP SE 38.85'
Punch cross in W end 24" CMP SW 31.49'
This corner is located by GPS measurement

Corner History:

6-1854 Michael Karrick, 80.00 set post for corner to sec. 26, 27, 34 and 35. No trees of suitable size for bearings therfor elected mound with trench, pitts, charred stake and Osage Orange seed at each angle.

3-1878 T. Hunter Pg. 331 No. 325 found stone set in previous survey (No. 301 unrecorded).

6-1887 T. Hunter Pg. 420 No. 409 found stone in center of road.

6-1932 J.Kerr (B.8 P.14 S.34) Pete Lee used stone to set N 1/4 34 M&L 5281.1. Meas South to fene line East 2637.3.

10-5-1970 County Surveyor found 120d in center roads of T intersection set 3-31-67.

10-15-1970 County Surveyor dug 4' West of 120d found limestone 4" x 5" on top 4" x 15" bottom 22" long with 3/4" x 4' iron on East side stone tilted East .7' out of plumb. Set stone vertical with rock weight on W side and glass and junk on E side with CIM on top.

10-28-1970 County Surveyor after finding S 34-35 decided limestone at 26-27-34-35 which leaned East near .7 should be removed and placed 06' East which would make line West 2639.7 to J.Kerr stone which was placed M&L 2640.55, then 2639.7 West to 27-28-33-34. Set CIM at new position.

10-4-2006 County Surveyor found CIM down 0.8' in good condition.