Certificate of Location of Government Corner

ID#: 652606 **Description:** 1/4 SEC COR 26 27 65 **Date Set:** 4/29/1968 **County:** Olmsted

Section: 26 **Township:** 106N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 3' north of centerline of CR 117 and in line with fence north
County highway disk in PP WNW 128.25'
5/8" rod under fence S 50'
This corner is located by GPS measurement

Corner History:

6-1854 Michael Karrick 40.00 set quarter section post. No trees of sufficient size for bearings, therefore erected mound with trench, pits, charred stake and Osage Orange seeds NE & SW.

3-1878 T. Hunter (P.331 No.325) found stake in center road avered by Mr. Fosdick as same as one in original mound and pits. Set stone 4 x 6 x 15 well down with 7 x 10 x 18 on top. 1/16 North set stake M&L 20.04-1/2 (1328.0) to corner in mound. 1/16 South set temp point M&L 19.90-1/2 (1313.73) for line West (N 1° E) to stone found set in previous survey. 1/16 West set boulder stone 4-1/2 x 9 x 28 M&L 20.09 (1325.94) N 89° 15W. 1/16 center NE 1/4 27 set stake inters lines (parties will set stone). 1/16 center SE 1/4 27 set stake inters lines. Stone found by A and Sankstone used J.Kerr 1967.

6-1887 T. Hunter (P.420 No.409) found stone. 1/16 East set stone M&L 19.84-1/2 (2629.77) dug extensively for this 1/16 with tractor, road in too sharp slope from East road gone to clay.

4-29-1968 J.Kerr as ground frozen 1967 dug deep to check validity of records placed CIM over top stone with sash weight by stone on North side. Also stone from adj field North of stone and monument. 6 x 8 x 30 very pointed lower than top of monument which is 8" below surface. Corner lies 7' from N edge road. 3' North of centerline bottle cap power pole WNW 128.25'. 5/8" x 2' rod under fence South 50.0'.

3-8-2000 County Surveyor found CIM down 0.6' in good condition.