Certificate of Location of Government Corner

ID#: 652704 **Description:** 1/4 SEC COR 27 34 65 **Date Set:** 8/30/1974 **County:** Olmsted

Section: 27 **Township:** 106N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 4 1/2' south of centerline of E-W twp road and 1' west of centerline of twp road north
County Survey Disk in top center 5" post SW 32.87'
County Survey Disk in CP NW 51.23'
This corner is located by GPS measurement

Corner History:

7-1854 Gov't Notes Michael Karrick, Deputy Surveyor, set quarter section post. 40.00 chs. West of Sec. Cor. 26-27-34-35 in mound with trench, pits, and charred stake and planted Osage orange seeds N.E. and S.W.

3-1878 Thomas Hunter (P.331 No.325) found stake remains. Set boulder 8"x15"x20" with another stone beneath. For 1/16 north set boulder 8"x12"x23" midway and on line.

6-7-1932 John Kerr (B.8 P.14) could not find corner. Set large boulder with broken stone and small stone around it.

10-1970 County Surveyor dug in area of corner and found gravel fill hole and 3.8' north the stone with small stones set by John Kerr. Accepted gravel hole as Hunter's corner since it fit the line and distance of Hunter's 1/16 stone north found in same survey. Drove 1" square x3' pine stake in hole.

8-30-1974 County Surveyor set 3/4"x18" rod beside wood stake and set C.I.M. over all.

3-8-2000 County Surveyor found CIM down 0.7' in good condition.