Certificate of Location of Government Corner

ID#: 652705 **Description:** SEC COR 27 28 33 34 65 **Date Set:** 3/10/2000 **County:** Olmsted

Section: 27 **Township:** 106N **Range:** 15W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 5' south of centerline of E-W twp road and 5' west of centerline of twp road south
SW end 18" CMP SW 37.90'
Bottle cap in NE side PP #7424 NW 69.5'
NE end 18" CMP NW 31.64'
Spike and BC in PP NW 69.50'
This corner is located by GPS measurement

Corner History:

6-1854 Michael Karrick, 80.00 set post for corner to sec. 27, 28, 33 and 34 erected mound with trench pitts, charred stake and Osage Orange seeds at each angle.

5-28-1928 J. Kerr Bk. 2 Pg. 37 found limestone on north side of road (4"x4" top with ridge in center).

6-7-1932 J. Kerr found stone. Ran line south for 1 mile.

1935 J. Kerr found stone at 1/16th south found iron bar.

10-5-1970 County Surveyor corner if any deep in tee road intersection.

10-16-1970 County Surveyor dug over 8' deep found logs, huge 4' round stone and 3' of rock fill before coming to clean black soil, found 4" x 4" top limestone as recorded by J.Kerr 5-1928 book 2 page 37. Set 1/2" iron over 1 1/4" pipe and original stone.

6-30-1972 County Surveyor set CIM over pipe found and checked.

1-14-1992 Vince Fangman took RP's 37.90 to SW end 18" CMP SW. 31.64 to NE end 18" CMP NW. 69.50 to spike and B.C. in PP NW.

3-10-2000 County Surveyor found pk down 0.1'. Removed. Found 1/2" x 10" pipe w/cap #14888 down 0.3'. Removed. Found CIM with head broken off down 2.5'. Set 2' telspar w/CIC over CIM down 0.3'.