Certificate of Location of Government Corner

ID#: 652906 **Description:** 1/4 SEC COR 29 30 65 **Date Set:** 10/15/1981 **County:** Olmsted

Section: 29 **Township:** 106N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of N-S twp road and 2' south of fence east
County Survey Disk in N side CP ENE 35.41'
Punch mark in lug N end CMP SW 79.29'
This corner is located by GPS measurement

Corner History:

1854 Gov't Notes Michael Karrick, Deputy Surveyor North between Section 29 and 30. 40.00 chs. Set quarter section post. Burr Oak 7 in. N34W 336 lks. Burr Oak 10 in. S78E 225 lks.

11-1857 E.P. Bircher, Surveyor, per J.B. Fellows, Deputy, (Old Road Book--Old Road 100) surveyed the road North and South at this corner.

3-14-1860 Samuel J. McDowell, Surveyor, (Book A, Page 64, No. 90) used this corner to set the Center 29.

5-1894 William Fraser (Book B, Page 92) "Could not find corner so drove stake on line and midway (39.82 chs.) between" Sec. corner 29-30-31-32, a stone and stake found, and Sec. corner 19-20-29-30, a stone set at proportionate Gov't measure between Sec. corner 29-30-31-32 and 1/4 corner 19-20 and at Gov't measure from the stump of a Brg. tree. He staked the N-S road between Sections 29 and 30.

10-15-1981 County Surveyor set a CIM over a 1/2"x18" rod midway and on line between the section corners as per Will Fraser's Survey B.92. Corner came in the center of the N-S road and 2' South of the line of newer fence East but only 1/2' South of old corner post still standing on the South side of the fence East. The measure North and South is 2626.85.

2-12-2010 County Surveyor found CIM down 0.5' in good condition.