Certificate of Location of Government Corner

ID#: 653104 **Description:** S 1/4 SEC COR 31 65 **Date Set:** 9/21/1981 **County:** Olmsted

Section: 31 **Township:** 106N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of E-W twp road and 2 1/2' west of fences north and south
County Survey Disk in SE side PP #8776 NE 39.84'
County Survey Disk in W side RR tie CP SSE 44.55'
County Survey Disk in SW side PP #95 NW 80.96'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes, John Ball Deputy Surveyor West between Section 6 and 31. 40.00 chs. Set post and drove charred stake for quarter section corner. Built mound with trench per instructions. Planted Osage Orange S.E. and Apple seed N.E. 79.95 chs. Set post and drove charred stake corner to Townships 105 and 106 North of Range 15 and 16 West 5th Mer. Built mound with trench per instructions. Planted Osage Orange S.E. and Apple seeds N.E.

9-18-1981 County Surveyor dug for this corner in line with the fences North and South and in the center of the E-W road but did not find anything.

9-21-1981 County Surveyor dug at the 1/16 West in line with the fence North which also came at prorated Gov't measure from S. Sec. Cor. 31-32 to S.W. Cor. 31. The road here had been cut to bedrock and we did not find anything. At the S. 1/4 Cor. 31 we set a Cast Iron Monument over 1/2"x18" rod on line and at proportionate. Gov't measure between the section corners. This corner is in the centerline of the E-W road and 2 1/2' West of fences North and South.

9-18-2002 County Surveyor found CIM down 0.8' in good condition.

4-8-2005 County Surveyor found CIM down 0.8' in good condition.