Certificate of Location of Government Corner

ID#: 653105 **Description:** SW SEC COR 31 65 **Date Set:** 9/30/1970 **County:** Olmsted

Section: 31 **Township:** 106N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of E-W twp road, in centerline of twp road north and in line with fence south
1¼" steel conduit pipe up 1" under W side of old fence S 100.0'
Bottle cap in NW side PP #8790 NE 43.13'
Bottle cap in SW side PP #8799 NW 74.43'
This corner is located by GPS measurement

Corner History:

10-1853 John Ball, 79.95 set post and droved charred stake corner to township 105 and 106 north of range 15 and 16. Built mound and trench, planted Osage Orange NE Apple seed.

1875 State law required monument be set at all township corners.

9-30-1970 County Surveyor found stone about 2.5' deep in road intersection and set 1 1/2"x12" iron pipe on NW side of stone and placed CIM over stone.

9-18-1981 1/16 N: County Surveyor dug down to top of stone found in 1970. Found stone down 2-1/2' in line with fence West and 3-1/2' West centerline N-S road. Stone 3.55' West and .85' South of the traverse nail. Set 5/8" rod at road surface.

9-18-1984 County Surveyor found CIM in good condition.

9-18-2002 County Surveyor found CIM down 0.7' in good condition.

4-8-2005 County Surveyor found CIM down 0.7' in good condition.