Certificate of Location of Government Corner

ID#: 653106 **Description:** W 1/4 SEC COR 31 65 **Date Set:** 9/28/1981 **County:** Olmsted

Section: 31 **Township:** 106N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 9' west of centerline of N-S twp road and 190' north of centerline of field entrance
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes John Ball, Deputy Surveyor North between section 31 and 36. 40.00 chs. Set post and drove charred stake for quarter section corner. Built mound with trench per instructions. Planted SE Osage Orange NE Apple seed.

9-30-1970 Olmsted County Surveyor dug at the SW corner 31 and found remaining 15" of 8"x8" square township monument. Removed CIM found 2.3 South and .9 East and reset is over limestone township monument. Dug at the 1/16 North with caterpiller and found stone monument in line with fence East and West. Dug at the W 1/4 corner 31 with caterpiller. Dug off entire road but did not find anything.

9-18-1981 Olmsted County Surveyor dug down to top of stone found in 1970 at the 1/16 South. Found stone down 2 1/2', in line with fence West 3 1/2' West of the centerline of the N-S road. Set 5/8" rod at road surface and over stone.

9-28-1981 Olmsted County Surveyor set a Cast Iron Monument over 1/2"x18" rod at double the line and measure from the SW corner 31 over the 1/16 North. The corner came 9' West of the centerline of the N-S road. There are no fences East or West. This corner is 9.16' West of the straight line between the section corners. We measured in the interior or both Section 31 and Section 36 but found nothing to dispute this position.

2-2-2010 Olmsted County Surveyor found CIM down 0.5' in good condition.