Certificate of Location of Government Corner

ID#: 653204 **Description:** S 1/4 SEC COR 32 65 **Date Set:** 5/11/2009 **County:** Olmsted

Section: 32 **Township:** 106N **Range:** 15W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 1' north of centerline of E-W twp road and 310' west of centerline of field entrance north
County Survey Disk in SW side PP WNW 95.24'
This corner is located by GPS reference stations "New Poles A & B"

Corner History:

10-1853 John Ball 40.00 set post and drove charred stake for quarter section corner. Built mound with trench per instructions. Planted SE Osage Orange NE Apple seed.

9-22&23-1981 County Surveyor, dug from the traverse nail, set on line from CIM at SW 32 to 5/8" rod set back at SE 32 as follows. by 5' deep to clay. Conditions only fair, found nothing. Digging to corner midway and also 2640' from SW 32. Should dig a little farther West to corner doubling 1/16 fence West.

10-29-1991 County Surveyor set corner M&L from CIM at SW 32 to re-rod at SE 32 for Kleinshcmidt survey in sec 32. Will place monument when we can get to it.

10-10-2003 V. Fangman set 1" pipe w/plastic cap RLS #14888 at Olmsted County Surveyor's location.

4-23-2009 County Surveyor found 1" pipe w/cap down 0.6' in good condition.

5-11-2009 County Surveyor found 1" pipe w/cap down 0.6' in good condition and verified location. Removed 1" pipe and set 5' telspar pipe w/Cast Iron Cap down 0.5'.