Certificate of Location of Government Corner

ID#: 653205 **Description:** S SEC COR 31 32 65 **Date Set:** 6/20/1966 **County:** Olmsted

Section: 32 **Township:** 106N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of E-W twp road and 2' east of centerline of N-S twp road
County highway disk in PP SW 46.87'
County highway disk in PP NW 44.15'
+ mark N end CMP NW 40.43'
+ mark S end CMP SW 37.3'
This corner is located by GPS measurement

Corner History:

10-1853 John Ball set post and drove charred stake corner to section 5,6,31 and 32. Built mound with trench per instructions. Planted SE Osage Orange NE Apple seed.

6-1895 W. Fraser 579-80 No.529 found stake in road used in setting NW corner 17. Set stone 2 x 10 x 18 and stake as corner. Meas South 239.55 record 239.85 or 19.85 then 19.97-1/2 then 39.95 5 times to SW corner 17 set no corners until NW corner 17.

1935 county highway department (B.75 P.74) found limestone with flat strap iron beside. Meas East 5293.0 could not find 1/4 corner. Fence post SW 34.6' tele SE 35.0'

6-20-1966 J. Kerr set CIM over stone found 6-1966 for road grade job of township.

5-21-2003 County Surveyor found CIM down 0.1' in good condition.

4-8-2005 County Surveyor found CIM in good condition down 0.3'. Did not check ties.

5-5-2009 County Surveyor found CIM down 0.3' in good condition.