Certificate of Location of Government Corner

ID#: 653404 **Description:** S 1/4 SEC COR 34 65 **Date Set:** 10/21/1975 **County:** Olmsted

Section: 34 **Township:** 106N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 10 1/2' south of fence east and in line with fences north and south
County Survey Disk in E side 6" Cedar NNE 86.4'
County highway disk in E side old fence post NE 11.2'
County highway disk in S side 12" Cottonwood NE 8.8'
County highway disk in SE side 12" Elm NNE 1.75'
Post w/sign 2' West
This corner is located by GPS reference stations "Noel A & B"

Corner History:

10-1853 Gov't Notes John Ball, Deputy Surveyor West between sections 3 and 34. 40.00 chs. Set post for quarter section corner. Burr Oak 5 in. N74E 201 lks. Burr Oak 5 in. S17E 86 lks.

6-7-1932 John Kerr (B.8 P. 14), County Surveyor, found corner fence post which rotted bearing tree stumps indicate is corner location.

12-1972 County Surveyor cound not find old post found by John Kerr. Set bottom piece of steel fence post midway and on line from the S.W Cor. Sec. 34 to S.E. Cor. Sec. 34. Corner in line of N-S fence.

10-21-1975 County Surveyor removed steel post and set C.I.M. over 1/2"x18" rod as corner midway and on line.

11-12-2002 County Surveyor found CIM at surface in good condition.

3-30-2005 Yaggy Colby Survey Crew found monument in good condition.