Certificate of Location of Government Corner

ID#: 653405 **Description:** S SEC COR 33 34 65 **Date Set:** 10/20/1970 **County:** Olmsted

Section: 34 **Township:** 106N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 3' west of centerline of twp road north and 2 1/2' north of centerline of twp road west
SW corner metal tele box No. 4 SE 64.28'
Bottle cap in W side PP #7391 SW 56.35'
This corner is located by GPS measurement

Corner History:

10-1853 John Ball 80.00 set post and drove charred stake corner to sections 3,4,33 and 34. Built mound with trench per instructions. Planted SE Osage Orange NE Apple seed.

6-7-1932 J. Kerr (B.8 P.14) found stone pointed out by local farmer (a limestone). Meas East to fence cor post proved by BT stump 2630.5. Meas North 5260 to stone.

1935 county highway department (B.75 P.74) found limestone 1' below road surface. Cherry tree E 24.9 meas West 2633.6 M&L. Cor fence post S 29.3.

10-6-1970 County Surveyor set nail and lath center roads N and W for line and meas North. Set nail at 2640 near edge woods West. Set nail at 3945 which came 1' S of fence E. Centerline road East 2891 ±. Total to nail 5268.4. Should meas from mon. at S 32.33 East check 2633.6 for S 1/4 33 con't to 5267.2. Believe stone near N-S of nail set E-W close.

10-9-1970 County Surveyor meas from S 32-33 set nail at 2633.6 on random line then meas 2635.85 to nail set previously.

10-20-1970 County Surveyor dug with tractor found stone easily a limestone (4"x8" top) about 2' deep in road. Set CIM over stone.

11-8-2002 County Surveyor found 1/2 pipe w/cap #14888 at surface. Removed pipe and found CIM down 1' in good condition.

3-25-2005 Yaggy Colby Survey Crew found monument in good condition.