# Certificate of Location of Government Corner

**ID#:** 653505 **Description:** S SEC COR 34 35 65 **Date Set:** 10/27/1970 **County:** Olmsted

**Section:** 35 **Township:** 106N **Range:** 15W **Monument Description:** Cast Iron Monument

**Reference Ties:**

The corner falls 5' north of fence west, 3' south of centerline of CR 126 east and 3' east of centerline of CR 126 south
Bottle cap in E side PP #7495 NNW 108.4'
Telephone cable post #29 NNW 119.9'
Bottle Cap in SW side PP #7495 SE 56.65'
Bottle Cap in SE side PP #7496 NE 49.58'
This corner is located by GPS measurement

**Corner History:**

10-1853 John Ball, 80.00 set post cor to sec 2, 3, 34 & 35. Burr Oak 5 S 35º E 247 links. Burr Oak 6 N 88º E 592 links, no other tree near, dug trench per instructions.

3-20-1889 T. Fraser unrecorded survey found limestone.

10-21-1970 County Surveyor meas from NE 34 South noting lines of fences and original 1932 meas of J. Kerr of N 1/2 2637.5. Set nail in line fence West at 5291.65 after finding 1/16 stone re-run line on data above, from true 1/16 over point 5.72' West of nail set on true proj line from NE 34 over 1/16 found. Set nail opposite original nail set at 5291.65 ignoring line of original nail.

10-27-1970 County Surveyor dug with tractor carefully top surface only removed. Found less than 6" shattered bottom original stone very plain with dark portion of original digging showing in clay clearly. Set CIM over RR spike set in bed rock after barring out much of top part original shell rock formation.

11-1-2002 County Surveyor found CIM down 0.5' in good condition.