Certificate of Location of Government Corner

ID#: 653609 **Description:** SEC CEN 36 65 **Date Set:** **County:** Olmsted

Section: 36 **Township:** 106N **Range:** 15W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

Reference Ties:

Corner History:

5-6-1873 T. Hunter (P.220 No.224) set stake at inters lines from all 1/4 corners. 1/16 West set stake M&L 19.99 N 89° 35 W. 1/16 North set stake M&L 20.04 N 1/4° E. 1/16 center NW 1/4 36 set stake true inters lines. 1/16 center SW 1/4 36 set stake true inters lines. 19.86 North to 1/16 corner between center and W 1/4 cor. 1/16 South set stake M&L 19.76 (1304.16) N 1/4° E. 1/16 East set stake M&L 19.98-1/2 N 89° 35 W. 1/16 center NE 1/4 36 set stake true inters lines.

10-1969 J. Kerr with McGhie assist, meas line from twisted rod by corner post at N 1/4 36 South. All lands South of brushy line where no definate fence in place 80 rods South owned on both sides by same owner. No hint of any line assist. Meas line carefully, set nail on offset line near existing N-S fence at 2645.28 a record meas. Set lath in fence to use as line in meas of East 80 rods of E-W 1/4 line to help set E 1/4 36. Corner would come somewhere in open field West likely about 22.8' or half of final offset at South end. As this line was 36.7' East true corner would be 13.9 West of nail or about 16' West of fence at that point set no record.

6-22-2000 Vince Fangman used computed center at intersecting quarter lines.

4-16-2003 Massey Land Surveying used computed center at intersecting quarter lines.