Certificate of Location of Government Corner

ID#: 700605 **Description:** W SEC COR 6 7 70 **Date Set:** 4/27/2004 **County:** Winona

Section: 06 **Township:** 107N **Range:** 10W **Monument Description:** 2" pipe with brass cap

Reference Ties:

The monument is at the surface.
The monument is 15' North of cornerpost for fences South and East
Post with sign 1' north
This corner is located by GPS reference stations "700605 A & B"

Corner History:

1853 Gov't Notes N. 80.00 chains set post for corner, dug trench. B.T.'s Blk Oak 14" N 56° W 110 links. Blk Oak 12" S 40° W 36 links. White Oak 14" N 25° E 19 links.

11-14-1900 (see field Bk 9 P.79-80) W.Fraser (P.691 No.614 S.1) County Surveyor Holdridge found old gov't stake. Tested NW and SW BT stumps and NE BT standing 14" White Oak N 25° E 19 lks. 1/16 north set indefinite point 19.85 M&L (field Bk says set stake and stake 10 chs west) for section corner set new stake with stone by side. 2-1/2" x 12" at top larger at bottom 24" long.

12-1923 Winona County Surveyor, E.C. Burns found corner as evidenced by stone. Placed 2" x 34" iron pipe.

4-27-2004 Winona County Surveyor, Pat Veraguth, found 3" x 19" x 20" stone. Removed the stone and replaced it with a 2" pipe with brass cap. Also found Burns' 2" pipe westerly 0.77'.

11-9-2012 Olmsted County survey crew found 2" pipe with brass cap in good condition. Found Burns' 2" pipe with mashed top up 0.6' and removed it.