Certificate of Location of Government Corner

ID#: 700606 **Description:** W 1/4 SEC COR 6 70 **Date Set:** 11/13/2012 **County:** Winona

Section: 06 **Township:** 107N **Range:** 10W **Monument Description:** Cast Iron Cap on Telspar Pipe

Reference Ties:

The monument is at the surface
The corner falls 17' NE of riverbank
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes: Set quarter sec. post. Original notes set at 40 chs N&S. 3-1/2 chs south of river 75 lks wide 30" oak on line S 6 lks. B.T.'s sugar 14" S 32° E 13 links. Elm 12" west 43 links.

11-14-1900 W. Fraser Book A, Pg. 691 No. 614 found small stake by side of large stump which we used for this survey but I was not satisfied, but left as found and ran random line as dated on plat, but nothing correct (see field book 9 Pg. 79-80 for W.F. full statement).

9-1923 E.C. Burns found the SE bearing tree and set a 1-1/2" x 30" Iron Axle. Tree sugar maple S 32° E, 13 links.

8-2007 Joel Thoreson, Assistant County Surveyor, Olmsted County, visited the area of the corner and found no survey monuments. The area is susceptible to flooding and aerial photos show the nearby river channel has moved from its previous location.

1-13-2010 Olmsted County survey crew staked out a position midway and on line betwwen section corners north and south. Also staked W. Fraser's full measure from the south (39.70 chains). Found no survey monument at either location. Found pieces of wire on the ground.

11-13-2012 Olmsted County survey crew set a 5.5' telspar pipe with cast iron cap at a computed location midway and on line between section corners north and south.