Certificate of Location of Government Corner

ID#: 701905 **Description:** W SEC COR 19 30 70 **Date Set:** 6/9/1992 **County:** Winona

Section: 24 **Township:** 107N **Range:** 10W **Monument Description:** 1" square pipe w/cap RLS #15809

Reference Ties:

The corner falls 8' east of N-S fence and under fence east
Chiseled hole in large stone N20ºW 13.52'
County Survey Disk in 4" Ash S36ºW 11.13'
County Survey Disk in 12" Burr Oak used as CP N70°W 8.21'
This corner is located by GPS measurement

Corner History:

6-1853 Gov't Notes John Ball, Deputy Surveyor North between section 25 and 30 80.00 chs. Set post for corner to sections 19,24,25, & 30. Burr Oak N73ºW 55 lks. Burr Oak S60ºW 37 lks. Burr Oak N42ºE 50 lks. Burr Oak S76ºE 100 lks.

10-1896 William Fraser County Surveyor (Page 595, No. 541) found pile of stones seeming to indicate corner, all four bearing tree stumps in place, measurement from bearing trees fell a little north of pile of stones, bearings did not correspond, so used measurements only. Drilled a hole in bedrock, placed a sheet of tin over, set a cedar stake in mound of ground over drill hole, took new bearing trees. 3" burr oak S84 1/2ºE 25 lks. 4" burr oak S39 1/2ºE 32 lks. Set a stake at 1/16th corner south 19.88 chs. Set a stone 3"x12"x24" at 1/16th corner west 19.95 1/4 chs.

6-9-1992 Olmsted County Surveyor found a u shaped iron, under this found 10" diameter piece of tin over drill hole in bedrock as set by William Fraser in 1896. This area is on a sidehill so stake and mound would have washed away. Set 16" long 1" square pipe w/cap driven into drill hole, packed stones around pipe. Found 3"x12"x24" stone at 1/16th corner west.

7-20-2009 Olmsted County Surveyor found 1" square pipe w/cap up 0.1' in good condition.