Certificate of Location of Government Corner

ID#: 703005 **Description:** W SEC COR 30 31 70 **Date Set:** 10/3/74 **County:** Winona

Section: 30 **Township:** 107N **Range:** 10W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 2' east of fence south and in centerline of CR 152
County Survey Disk in E side CP S 24.34'
County Survey Disk in NE side PP SE 32.20'
40d nail in E side Ash S 141.2'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes, Elisha Norris, Deputy Surveyor North between sections 36 and 31.
80.00 chs. Set post in mound with pits and trench and deposited charred stake and Hawthorne seeds.

10-1896 William Fraser (P. 595 No. 541), County Surveyor, states corner gone. Mr. Fay and Mr. Small avered stake lay in line with fences north and south. Ran township line from E. 1/4 corner 25 south to township corner. Corner came in center of road and lined with fences. Set stone 6"x12"x14" with stake driven by side on line.

10-3-1974 Olmsted County Surveyor dug and found 1 1/2" pipe 18" deep and a stone 5" x 6" x 12" laying down. Dug around stone and found a definite stake hole. Drove a 1 1/2" pipe in the stake hole and placed the stone on south side and placed C.I.M. over all.

6-27-1994 Olmsted County Surveyor found C.I.M. in good condition.

12-11-2000 Olmsted County Surveyor found CIM down 0.7' in good condition.