Certificate of Location of Government Corner

ID#: 703006 **Description:** W 1/4 SEC COR 30 70 **Date Set:** 12/1/23 **County:** Winona

Section: 30 **Township:** 107N **Range:** 10W **Monument Description:** 2" pipe

Reference Ties:

The monument is up 0.5'
The corner falls on SW side of CP to fences north and east
8" Burr Oak WSW 12.0'
Post w/sign 1' north
This corner is located by GPS reference stations

Corner History:

1853 Gov't Notes: N 40.00 chains set quarter section post. B.T.'s - Burr Oak 10" west 76 links, Burr Oak 10" S50°E 103 links. "H" found corner post fo fence put in center of mound in place of stake. Mr. S. Fay said he put the post in place of stake when the stake was standing. Found the stump of the west B.T. and found that the corner corresponded in msmt but not in course with old U.S. Field notes. Set stake marked 1/4 S east side of post.

10-1896 W. Fraser (P.595 No.541) found corner fence post inmound placed by Mr. S. Fay in place original stake, stump of west B.T. checked meas but not course. 2 original B trees 10" Burr Oak west 76 lks 10" Burr Oak S50°E 103 lks. 16 north set stake M&L 19.88 1312.08'. 16 south set stake marked M&L 19.98-1/3 1318.9'

12-1923 E.C. Burns 2"x34" pipe

10-8-1974 Olmsted County Surveyor found 1-1/2" pipe on SW side of corner post. RP's 8" Burr Oak WSW 12.0'.

6-5-1992 Olmsted County Surveyor found Burns pipe in good condition. Fences N-E set sign and post 1.0' north.

8-24-2010 Olmsted County survey crew found 2" pipe in good condition