# Certificate of Location of Government Corner

**ID#:** 703106 **Description:** W 1/4 SEC COR 31 70 **Date Set:** 10/25/94 **County:** Winona

**Section:** 31 **Township:** 107N **Range:** 10W **Monument Description:** Cast Iron Cap on telspar pipe

**Reference Ties:**

The monument is up 0.6'
The corner falls 1' south of CP to fences N-S-E-W
Post w/sign 1' NE
This corner is located by GPS measurement

**Corner History:**

1853 Gov't Notes: N 40.00 chains, set quarter section post in mound with pits and trench and deposited charred stake and hawthorn seeds.

10-25-1994 Olmsted County Surveyor dug from C.P. to 4 way fence south to cover M&L. W.F. in split mile and one half into thirds. This is a filtered in area with hill to north. We found a piece of pottery 4" x 6" nearly vertical near a dark spot 1-1/2' deep. We dug deeper at 2-1/2' deep we found 4" of stake in a 2" diameter mark which ran into clay at 3' deep. Running another 3" to a point before disappearing. Set cast iron cap on telspar pipe at stake and pottery location. Removed to office. The corner lines with main fence E-W-N-S and falls ± 1' south of C.P. to 4 way fence. Drove post and sign NE'ly of monument.

8-23-2010 Olmsted County survey crew found CIC in good condition