Certificate of Location of Government Corner

ID#: 710106 **Description:** 1/4 SEC COR 1 2 71 **Date Set:** 6/30/1977 **County:** Olmsted

Section: 01 **Township:** 107N **Range:** 11W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The monument is down 0.2'
The corner falls on east bank of ditch (7' east of centerline of ditch)
County Survey Disk in E side 8" blazed Basswood SE 11.84'
County Survey Disk in E side 6" Walnut S 12.9'
1/2" pipe up 2' on south side
This corner is located by GPS reference stations.

Corner History:

10-1853 Gov't Notes William A. Jones, Deputy Surveyor South between Sections 1 and 2 39.85 chs. Set a quarter section post from whence a Bur Oak 6 in. diam. N25°E 6 lks Bur Oak 8 in. diam. S65°W 44 lks 79.85 chs. To section corner.

10&11-1900 William Fraser (P. 692-8 No. 615 and Field Book 9 P. 61-68) County Surveyor, found a stake set by Mr. Olds, a surveyor, but as both bearing trees standing plainly marked placed the corner 8 lks. East and South, drove a red cedar stake at the correct corner and piled rocks around it. Also set the W 1/4 Corner 2 and the Center 2.

6-30-1977 County Surveyor could not find the stake set by Fraser but found a 12" Bur Oak, with blazes, growing in rock on the West bank of a deep wash and accepted it as the S.W. Gov't bearing tree. Set a Cast Iron Cap on a square pipe packed in rock at Gov't measure from the bearing tree and on the line from the W 1/4 Corner 2 (found) over the Center 2 (found). Set a 1/2" pipe (up2') on the South side of the monument.

3-15-2010 County survey crew found cast iron cap on square pipe in good condition

12-30-2010 County survey crew found cast iron cap on square pipe in good condition.

5-19-2011 County survey crew found cast iron cap on square pipe in good condition.