Certificate of Location of Government Corner

ID#: 710304 **Description:** 1/4 SEC COR 3 10 71 **Date Set:** 10/15/2008 **County:** Olmsted

Section: 03 **Township:** 107N **Range:** 11W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 38' west of fence north, 18' west of centerline of twp road south and 8' north of fence west
County Survey Disk in NW side 5" cresoted CP ESE 38.73'
County Survey Disk in NE side 5" cresoted gate post SE 12.19'
Sign on fence post 8' south
This corner is located by GPS measurement

Corner History:

9-l853 Gov't Notes William A. Jones, Deputy Surveyor. Set a post 39.935 chains west of Section Corner 2-3-10-11 in mound of earth and sod. Deposited charcoal, made trench, dug pits and planted osage orange seed north and south of trench.

1900 William Fraser (P. 692-8 No. 615), County Surveyor, states corner and all evidence gone. Set stone 4" x 9" x 14" midway and on line on top of 1" x 2 1/2' iron bolt.

9-10-1974 County Surveyor dug and found bolt set by William Fraser 1' deep. Set a shortened piece of C.I.M. over the bolt flush with the surface.

10-15-2008 County Surveyor found CIM down 0.4' leaning west. Removed CIM and found 1" x 3' bolt down 1.3' in good condition. Removed bolt and set 5' telspar pipe w/cast iron cap down 0.2' at bolt position. Set sign on fence post.