# Certificate of Location of Government Corner

**ID#:** 710306 **Description:** 1/4 SEC COR 3 4 71 **Date Set:** 4/12/2010 **County:** Olmsted

**Section:** 03 **Township:** 107N **Range:** 11W **Monument Description:** Cast Iron Cap on telspar pipe

**Reference Ties:**

The corner falls 33' west of centerline of N-S ditch, 10' west of N-S fence and 6' south of E-W fence
The monument is up 0.4'
County Survey Disk in SE side 3" Pine N20°E 19.35'
County Survey Disk in N side blazed 24" Pine S74°W 20.23'
County Survey Disk in S side 7" White Oak E 18.49'
Square pipe (up 3') S 1' and 1"x22" pipe N 1'
This corner is located by GPS measurement

**Corner History:**

10-1853 Gov't Notes William A. Jones, Deputy Surveyor South on true line between sections 3 and 4. 39.97 chs. Set a quarter section post from whence a White Oak 6 in. diam. N20°E 11 lks White Oak 14 in. diam. S62 1/2°W 19 lks 79.97 chs. To section corner.

12-1891 Thomas Fraser (P. 467 No. 449, County Surveyor, states he found the NE and NW bearing trees and a stake a Mr. Wedge had found lying down and had set up again. The bearing trees placed the corner 3 lks. further West so set a new stake by the bearing trees.

10 & 11-1900 William Fraser (P. 692-8 No. 615 and Field Book 9 P. 81-82), County Surveyor, found "stake and tested by bearing tree standing and the stump of the NE bearing tree which had the marks on it plain. Drove red cedar stake not marked."

9-14-1977 County Surveyor found a 1" x 22" pipe (up 6") and the remains of a cedar stake. Removed the pipe and stake and set a Cast Iron Cap on a square pipe (up 6") as the corner. Set a square pipe (up 3') 1' South of the corner and set the pipe found 1' North of the corner.

3-2-2010 County Survey Crew found Cast Iron Cap on telspar pipe up 0.7' leaning SE.

4-12-2010 County Survey Crew found CIC/p2 leaning SE, plumbed up monument and checked w/3 remaining ties. Determined to be good positioin. Set 3 1/2' telspar pipe w/CIC up 0.4'.