Certificate of Location of Government Corner

ID#: 710404 **Description:** 1/4 SEC COR 4 9 71 **Date Set:** 8/1/1990 **County:** Olmsted

Section: 04 **Township:** 107N **Range:** 11W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 22' east of old CP to fences south and west
County Survey Disk in 17" Boxelder WNW 16.14'
County Survey Disk in CP WSW 24.65'
County Survey Disk in 6" White Oak SSW 12.51'
Post w/sign 1' west
This corner is located by GPS reference stations "Dove A & B"

Corner History:

9-1853 Gov't Notes. William A. Jones, Deputy Surveyor West on true line between sections 4 and 9 40.00 chs. Set quarter section post in mound of earth and sod, deposited charcoal, made trench and pits, planted osage orange seeds north and south of trench.

10-1893 William Fraser, Deputy County Surveyor (Page 538, No. 499), found stone set by Thomas Fraser where original stake stood. Set 1/16 stake 20.31 1/4 chs. east then 20.31 ¼ chs. to section corner 3, 8, 9, 10. Set 1/16 stake 19.76 chs. south then 19.76 chs. to center which was set midway and online between north and south quarter corners.

10-1900 William Fraser, County Surveyor, (Page 692 No. 615). Upon measuring found section corner 3, 4, 9, 10 used in 1893 as not correct.

8-1-1990 County Surveyor dug and found stone set by Thomas Fraser and used by William Fraser in 1893. Found stone 4" deep, 8" X 12" X 14", under stone found stake mark. Set telspar pipe with cast iron cap over stake mark.

10-3-2008 County Surveyor found cast iron cap on telspar pipe up 0.5' in good condition.