Certificate of Location of Government Corner

ID#: 710506 **Description:** 1/4 SEC COR 5 6 71 **Date Set:** 11/29/1979 **County:** Olmsted

Section: 05 **Township:** 107N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in line with fence west, 1' south of fence east and 1 1/2' west of centerline of N-S twp road
County Survey Disk in SW side gate post NW 27.15'
County Survey Disk in N side PP #33002 ESE 18.92'
This corner is located by GPS measurement

Corner History:

10-1853 Gov't Notes William A. Jones, Deputy Surveyor South on true line between sections 5 and 6. 40.29 chs. Set a quarter section post in mound of earth and sod. Deposited charcoal, made trench and pits, planted Osage Orange seed E & W of trench. 80.29 chs. To section corner.

11-29-1979 County Surveyor dug for this corner with the backhoe. Found a ragged rust colored boulder 2.2' deep that had been dug in. We put 3/4" bent irons on the East and West sides of the stones and set a C.I.M. over the stone at the road surface. We also found a threaded iron at the road surface 1.9' East and .1' North of the C.I.M. We did not replace this iron after digging.

12-15-2005 County Surveyor found CIM down 0.6' in good condition.