Certificate of Location of Government Corner

ID#: 710604 **Description:** 1/4 SEC COR 6 7 71 **Date Set:** 1/13/2006 **County:** Olmsted

Section: 06 **Township:** 107N **Range:** 11W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 3' west of N-S fence and 2' north of fence east
Sign in CP 3 1/2' SE
This corner is located by GPS reference stations "Petit A & B"

Corner History:

1853 Gov't Notes, W.A. Jones set 1/4 section corner post 40 chs west of 5-6-7-8 total mile S line 6 79.92 5274.72 west 1/2 2634.72' west 1/4 1314.72. Corner could be in fairly narrow high level area sloping rather sharply both east and west. No road, farm lines N-E-S common land west made mound of stone around corner.

6-1877 Hunter (P.317 No.311 S.7) G.W. Smith found stake with stones piled around it, which Mr. Leachout and other settlers aver as where original corner stood, no meas.

11-1891 Thos. Fraser (P.460 No.444 S.7) S.Jinks, Evens, C.Hollenbeck, found stake in mound of stones P.317. 16 S set stake M&L 19.82-5/8 1308.53. 16 center NE 1/4 7 set iron stake M&L on E-W 1/16 line 19.91-1/4 1314.2'.

11-21-1979 County Surveyor found two large old posts here. One post standing and in line with fences N-E-W. The other post rotted off and lying down stood 2' north. We dug 3' diameter around each post but found nothing. Practically no dirt over bedrock here. Could find no particular mound of stone as called for here.

12-16-2005 County Surveyor did not find any monument. Set 120d spike 2' west of N-S fence and 2' north of E-W fence and assumed located.

1-13-2006 County Surveyor scraped and dipped from 6' north to 10' north and 2' east to 6' west of CP to cover Gov't full measurement. Found nothing. Scraped and dipped from 6' south to 14' south and 2' east to 6' west of CP to cover T. Fraser full measurement. Found fence south and 1979 CP lying down. Found nothing further. Set 5' telspar pipe w/cast iron cap at oldest CP position found in 1979. Set sign in CP.