Certificate of Location of Government Corner

ID#: 710706 **Description:** W 1/4 SEC COR 7 71 **Date Set:** 6/11/74 **County:** Olmsted

Section: 07 **Township:** 107N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of N-S twp road and in line with fences east and west
Bridge bolt 8" North of fence W 60.0'
County Survey Disk in CP E 42.8'
Punch hole in S end 12" CMP SW 38.65'
Punch hole in S end 12" CMP SE 38.08'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes, John Ball, Deputy Surveyor 40.00 chs. Set quarter section post. Burr Oak 10 in. N25°E 266 lks Burr Oak 12 in. S66°W 378 lks

6-1877 Thomas Hunter, County Surveyor, states bearing trees completely grubbed out. Found stone planted in ground where quarter post stood.

6-1902 Robert Fraser (Old field book #10, P. 44), County Surveyor, found a boulder stone in center of road and in line with fence running west.

8-16-1972 County Surveyor dug by hand on the testimony of a Mr. Evans, a local land owner, and found a boulder.

6-11-1974 County Surveyor set a C.I.M. over the stone with a 1/2" x 12" rod under the monument and took references.

12-15-2005 County Surveyor found CIM down 0.5' in good condition.