Certificate of Location of Government Corner

ID#: 710709 **Description:** SEC CEN 7 71 **Date Set:** **County:** Olmsted

Section: 07 **Township:** 107N **Range:** 11W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

Reference Ties:

This corner is located by GPS reference stations "McDougall A & B"

Corner History:

6-12-1877 T. Hunter (P.317 No.311) set stake at true inters lines. 8" Jack Oak N 37-1/2°W 30-1/2 lks 20.1'. 6" Jack Oak S 48°W 6-1/2 lks 4.3'. 1/16 west set stake line and 19.93-3/4 (1315.86) then 19.69-1/4 1299.7'. 1/16 east set stake stone M&L 19.94-1/2 1316.37'. E-W 1/4 line N 89-3/8°W N-S 1/4 line N 23' E.

11-8-1891 Thos. Fraser (P.460 No.444) found SW BT and NW BT stump and hole where stake had been. Stake had been placed 4' NE by someone. Placed stake in old hole and new stake by side as originally placed by Hunter P.317. 1/16 north set stake 19.82-5/8 M&L to known 1/4 corner. 1/16 corner center NE 1/4 7 set iron stake 19.91-1/4 M&L on EW 1/16 line.

1-11-2006 County Surveyor visited area of corner. Found CP to fences N-W-E.

1-11-2006 Center NE 1/4: County Surveyor scraped and dipped from 30' west to 33' west of CP. Found nothing.

1-12-2006 1/16th E: County Surveyor scraped and dipped from T. Hunter's full measure to 4' east. Found nothing.

1/16th N: County Surveyor scraped and dipped from CP to 10' south. Found nothing.