# Certificate of Location of Government Corner

**ID#:** 710805 **Description:** SEC CEN 7 8 17 18 71 **Date Set:** 9/3/2002 **County:** Olmsted

**Section:** 08 **Township:** 107N **Range:** 11W **Monument Description:** 1" square pipe w/cap RLS #15809

**Reference Ties:**

The corner falls 1/2' south of centerline of CSAH 2
County Survey Disk in NE side PP #33254 (up 6') NW 135.5'
County Survey Disk in S side PP #33255 (up 6') NE 185.5'
Orange painted steel post (top N edge) S 49.15'
This corner is located by GPS measurement

**Corner History:**

1853 Gov't Notes: W.A. Jones set section corner post 80 chs north of 17-18-19-20. 8" Burr Oak N 86E 545 lks 359.7. 12" Burr Oak S 90E 716 lks 472.6. Stream 10 lks wide course NE north 4.50 chs 297'. Stream 5 lks wide course NE west 5.09 chs 335.9'. Corner in EW county road #2 common lines north of farms farm line N 80 rods W farm line S 80 RE.

11-1891 Thos. Fraser (P.459 No.443 S.17) Geo Smith found stone set by Hunter when all B trees were in place etc. Meas east 39.79-7/8 to 1/4 cor stone.

11-1892 Thos. Fraser (P.500 No.477 S.18) H.Davidson, J.Harvey, Perves, corner verified but not used.

6-1877 Hunter (P.347 No.311 S.7) G.W. Smith found stone planted in road both witness trees standing, Mr. G.W. Smith swears under oath stone set exactly where original stake was standing when he set stone.

10-1962 county highway department 2 x 2 hub and nail latest ties 1965 B226. Hub S 48.73 fron to top steel FP orange top S 48.88. Hub SW 56.97 front of top steel FP orange top SW 58.13. Hub SE 61.16 front of top steel FP orange top SE 60.74. Co. H.D. (B.226 P.15) set CIM in 11-1963. Meas west 2631.57 R2636 P.313. Meas east 2636.05 R2626.8 P.459. Note this corner assumed, 1/4 corners east and west are stones found. Use discusion as to this corner.

9-24-1974 County Surveyor dug 8' deep in C.R. #2 and found the recorded stone 1.45 E and 0.4' north of the CIM set by county highway department. Placed iron around the stone and pieces of blacktop. Set a 1/2" rod under the CIM. Corner lies in the centerline C.R. #2 with no fences running north or south. RP's: C.S. disc NE side PP #33254 (up 6') NW 135.5'. C.S. disc S side of PP #33255 (up 6') NE 185.5'. Orange painted steel post (top N edge) S 49.15.

5-10-2002 County Surveyor set 1" square pipe w/cap as ref. For 2002 overlay. Tied out corner.

5-24-2002 County Surveyor removed CIM and found stone down 2.6'.

9-3-2002 County Surveyor set 1" square pipe w/cap over p.k. nail at surface.

12-15-2005 County Surveyor found 1" square pipe w/cap at surface in good condition.

3-6-2007 County Surveyor found 1" square pipe w/cap at surface in good condition.

1-15-2008 County Surveyor found 1" square pipe w/cap at surface in good condition.