Certificate of Location of Government Corner

ID#: 711004 **Description:** 1/4 SEC COR 10 15 71 **Date Set:** 8/28/2002 **County:** Olmsted

Section: 10 **Township:** 107N **Range:** 11W **Monument Description:** 1" square pipe w/cap RLS #15809

Reference Ties:

The corner falls 17 1/2' east of centerline of twp road north, 4' east of centerline of twp road south and 11' south of centerline of CSAH 2
County Survey Disk in PP #1246 NW 73.72'
Top center of telephone riser box NE 61.4'
NE edge of 8" square concrete fence post SW 55.61'
County Survey Disk in PP #1247 SE 114.98'
Ref pipe SW 80.92'
This corner is located by GPS measurement

Corner History:

9-1853 Gov't Notes William A. Jones, Deputy Surveyor, set a post 39.965 chs. west of Section Corner 10-11-14-15 in mound of earth and sod. Deposited charcoal, made trench and pits, and planted osage orange seeds north and south of trench.

10-1900 William Fraser, County Surveyor, (P.692-8 No.615) states corner lost. Placed stone 8"x8"x24" running to point with stake on north side midway and on line.

9-11-1974 County Surveyor dug with backhoe and found recorded stone and stake. Set C.I.M. over stone.

5-10-2002 County Surveyor set 1" square pipe w/cap as ref. For 2002 overlay. Tied out corner.

5-29-2002 County Surveyor removed CIM and found rod down 2.1'.

8-28-2002 County Surveyor set 1" square pipe w/cap over p.k. nail at surface.

12-12-2006 County Surveyor found 1" square pipe w/cap at surface in good condition.

3-6-2007 County Surveyor found 1" square pipe w/cap at surface in good condition.