Certificate of Location of Government Corner

ID#: 711005 **Description:** SEC COR 9 10 15 16 71 **Date Set:** 9/11/74 **County:** Olmsted

Section: 10 **Township:** 107N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 38' NW of centerline of CSAH 2 on curve
County Survey Disk in W side TP stub NE 36.73'
County Survey Disk in PP SW 51.80'
Top NW corner concrete CP SE 77.44'
Post w/sign 1' NW
This corner is located by GPS measurement

Corner History:

9-1853 Gov't Notes, William A. Jones, Deputy Surveyor, set a corner post 80.0 chs. north of Section Corner 15-15-21-22 in a mound of earth and sod. Deposited charcoal, made trench and pits and planted osage orange seed N.W. and S.E. of trench.

10-1900 William Fraser (P. 692-8 No. 615), County Surveyor, states corner lost. Set stone 4"x9"x30" according to Gov't measure.

1928 John Kerr (B.-1 P. 19-22), County Surveyor, found large hole where stone had been dug out. Placed 7' steel post as corner.

9-11-1974 Roger Brand, County Surveyor, dug with backhoe and found steel post set by Kerr in 1928. Put a boulder beside post and C.I.M. Corner is .95' north of a straight line from the east (S.E. Cor. 10 over S.1/4 Cor. 10).

7-5-90 County Surveyor found C.I.M. on north ditch slope, set survey marker sign on post ± 1' NW, took new ties.

12-12-2006 County Surveyor found CIM in good condition.

3-6-2007 County Surveyor found CIM down 0.5' in good condition.