Certificate of Location of Government Corner

ID#: 711405 **Description:** SEC COR 14 15 22 23 71 **Date Set:** 8/3/1992 **County:** Olmsted

Section: 14 **Township:** 107N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 4' south of centerline of E-W twp road, 1 1/2' west of centerline of twp road south and in line with fence north
Spike in Oak SE 54.50'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes, William A. Jones, Deputy Surveyor north between sections 22 and 23. 80.00 chs. Set section corner post. Made mound, pits, trench, and planted osage orange deposited charcoal.

6-1885 Thomas Hunter (P. 399, Book A), County Surveyor, found old stake in center of road in line fence East. Drove new stake "well down" with boulder stone on top.

10-1900 William Fraser (P. 692 to 697 Book A), County Surveyor found corner described P. 399.

1933 County Highway Department (Book 73, P. 74) found boulder about 6" deep in line with fence north and row of trees east.

7-2-1973 Roger Brand, County Surveyor, found large boulder and set CIM over it.

6-15-1992 County Surveyor found CIM leaning North.

8-3-1992 County Surveyor dug out CIM and reset it over stone found 1973.

10-13-2008 County Surveyor found CIM down 0.6' in good condition.