Certificate of Location of Government Corner

ID#: 711406 **Description:** 1/4 SEC COR 14 15 71 **Date Set:** 10/9/2003 **County:** Olmsted

Section: 14 **Township:** 107N **Range:** 11W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 1' west of N-S fence, 1' north of fence east and in line with fence west
Sign on CP 1' east
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes: Wm. A. Jones, set 1/4 section corner post M&L 40 chs 2640', corner is boundary corner 4 farms. Corner in clear medium slope area, wide conours almost crest likely slight slope north toward high crest.

10-1900 W.Fraser (P.692-7 No.615 S.2-3-11) 9 parties see NE 2, found stake west side corner fence post not marked left as found. Meas 39.70 north to section corner 2620.2'. Meas 39.94 south to section corner 2636.04'.

1900 W.Fraser Book 9 Page 75 "I", found stone with stake by side on line with fences running north and south and claimed to be where Gov't corner stood.

10-8-2003 County Surveyor dug 1/2' North x 2' West x 2' East x 3 1/2' South of 1992 shot position to cover W. Fraser prorated distances N-S. Found charred wood pieces down 2 1/2' in dirt/clay mix. Found 6" dia. Dark spot in clay below wood pieces down to 3 1/2' deep before disappearing. Found smaller dark spot below first dark spot tapering to a point down 3.8'.

10-9-2003 County Surveyor set 6' telspar pipe w/cast iron cap up 0.1' at dark spot location. Set sign on CP.

12-30-2008 County Surveyor found telspar pipe w/CIC down 0.6' in good condition.