Certificate of Location of Government Corner

ID#: 711504 **Description:** 1/4 SEC COR 15 22 71 **Date Set:** 10/13/2008 **County:** Olmsted

Section: 15 **Township:** 107N **Range:** 11W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls in centerline of E-W twp road, in centerline of twp road north and 1' east of fence south
Concrete nail in W side 8" leaning concrete CP S 28.82'
This corner is located by GPS measurement

Corner History:

9-1853 Gov't Notes William Jones, Deputy Surveyor West on true line between sections 15 and 22. 39.975 Set a quarter section post in mound of earth and sod and deposited charcoal. Made trench and pits and planted osage orange seeds north and south of trench.

6-1885 Thomas Hunter (P. 399 No. 389), County Surveyor, found old stake in ground in line of fence West. Set new marked stake.

9-28-1974 County Surveyor dug with backhoe 1 1/2' deep and found old stake (about 6"). Drove a 3/4" x 15" rod in hole and set CIM over all.

10-13-2008 County Surveyor found CIM down 1.5' in good condition. Removed CIM and found 3/4" rerod down 3.1' in good condition. Removed 3/4" rerod and set 5' telspar pipe w/cast iron cap down 0.6' at 3/4" rerod position.