Certificate of Location of Government Corner

ID#: 711505 **Description:** SEC COR 15 16 21 22 71 **Date Set:** 6/21/2011 **County:** Olmsted

Section: 15 **Township:** 107N **Range:** 11W **Monument Description:** Copper plug in concrete road

Reference Ties:

The corner falls 0.1' east of centerline crack of CSAH 1 and 3' north of centerline of township road east.
The monument is at the surface.
This corner is located by GPS reference stations "Ref iron 711505 and Dayton"

Corner History:

1853 Gov't Notes: Wm.A.Jones, set section corner post 80 chs north of 21-22-27-28. 10" Burr Oak N80°E 500 lks 330.0, 9" Burr Oak S25W 477 lks 314.8. N NE'ly center blacktop #10 and corner in sharp ravine sloping corner in inters N-S county road twsp road east, common land west.

10-1900 W.Fraser (P.692-8 No.615 S.2-3-11) 9 parties see NE 2 (see W.F. field bk 9 p.68-79). A corner avered to have stood in center road in line fence west by Mr. F.B. Thompson. Dug 5' deep 8' square, a meas of section line E 1/4 22 north to NW 10 places. Corner 2 links north of fence, a stump assumed to be SW BT places point very near this spot. Placed no corner.

1945 C.H.D (B.168 P.14) stake over stone found. Spike disc top corner fence post NW 44.11, spike disc top power pole SW 45.15.

10-1974 County Surveyor dug with backhoe 10' deep 6' E&N x 8' N-S did not find stone as called for by Co. Hwy. Dept.

8-29-2008 Rod Berg, Olmsted County Survey Department, computed a coordinate position based on measurements to nearby section corners and information found on old highway plans. This position was then used to prepare right of way plats for CSAH 10.

6-21-2011 County survey crew set a copper plug in concrete road using previous coordinates computed by Rod Berg.