Certificate of Location of Government Corner

ID#: 711606 **Description:** 1/4 SEC COR 16 17 71 **Date Set:** 9/1/1974 **County:** Olmsted

Section: 16 **Township:** 107N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 2' south of fence west, 3' east of fence south and 4' SE of Oak used as CP to fences south and west
40d spike in Oak ESE 35.35'
Post w/sign 2' south
This corner is located by GPS reference stations "LVA A & B"

Corner History:

9-1853 Gov't Notes William Jones North between sections 16 and 17. 40.00 chs. Set a quarter section post in a mound of earth and sod. Deposited charcoal and made trench and pits and planted osage orange seed east and west of trench.

11-1891 Thomas Fraser (P.459 No.443), County Surveyor, found post said set by Samuel Kepner by side of original gov't stake in mound.

6-1895 William Fraser, County Surveyor, (P.575 No. 526) found post. Removed post and set 2 stones as corner.

9-13-1974 County Surveyor found 3 pieces of limestone lying flat about 3' S.E. of large Oak tree used as fence corner. Dug large hole by hand under stones about 18" deep and found 1½"x6" deep hole with old wood remains in it. Set 3/4"x20" iron rod in stake hole and set C.I.M. over rod and about flush with ground and placed the pieces of limestone around the top of monument.

10-16-2008 County Surveyor found CIM up 0.1' in good condition. Set post w/sign.