Certificate of Location of Government Corner

ID#: 711706 **Description:** 1/4 SEC COR 17 18 71 **Date Set:** 6/3/2013 **County:** Olmsted

Section: 17 **Township:** 107N **Range:** 11W **Monument Description:** Cast Iron Cap on Telspar Pipe

Reference Ties:

The monument is down 1'
The corner is located in common area with no fence near
This corner is located by GPS reference stations "Doberman A & B"

Corner History:

1853 Gov't Notes: Wm. A. Jones, set 1/4 section corner post M&L 40 chs 2640. Farm lines W&S common N&E corner in wide low level bottom lands.

11-6-1891 T. Fraser (Book A, P.459 No.443 S.17) found marked stake in place avered by G. Hinton to be exact spot gov't corner, stood and undisputed.

11-1892 Thos Fraser (Book A, P.500 No.471 S.18) found marked stake P.459 beside corner post. 1/16 west drove iron bolt M&L 20.01-1/2 1321'. 1/16 cor center SE 1/4 18 iron bolt set M&L 20.01-1/2 N-S 1/16 line, meas south 40.02 to section corner. In setting SE 18 found meas from 1/4 17-18 to 1/4 19-20 overran 4 lks so measure south to SE 18 40.02 or 2641.32'.

4-4-1973 County Surveyor walked to corner with eletronic prism, set up 16' east behind gate post of fence east for elec meas south, found 4" very old post just north of 10" rotted off corner post of fences S-E-W. Broke glass on top of old post stub, results of meas south to 1/4 19-20 found 5268.97, record M&L 40.02 or 5282.64 or 13.67 over actual.

4-5-1973 County Surveyor found iron bolt west as 1/16 set by T. Fraser (Book A, P.500, No. 471) M&L 20.01-1/2 1321.0' 1/4 17-18 post stub S 2638.29 then 2630.68 to stone at 1/4 19-20.

12-4-2009 County survey crew found iron bo;t at 16th corner west

6-3-2013 County survey crew set 5' telspar pipe with cast iron cap at the computed position of the old post found in 1973.