Certificate of Location of Government Corner

ID#: 711805 **Description:** W SEC COR 18 19 71 **Date Set:** 11/8/76 **County:** Olmsted

Section: 18 **Township:** 107N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 1' S of E-W fence
County Survey Disk in SW side 17" Box Elder NW 11.77'
County Survey Disk in N side 5" blazed Box Elder ENE 33.72'
County Survey Disk in E side blazed 9" Burr Oak (tie across small field) SW 217.43'
Post w/sign 1' west
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes John Ball, Deputy Surveyor North between sections 19 and 22. 80.00 chs. Set post corner to sections 13,18,19, and 24. Burr Oak 10 in. N52°W 162 lks. Burr Oak 6 in. N30°E 83 lks. Burr Oak 10 in. S88°E 14 lks. Dug trench.

11-1892 Thomas Fraser (P. 500 No. 477), County Surveyor, states corner gone. Set a 5" x 10" x 30" stone midway and on line from the N.W. Cor. Sec. 18 to the S.W. Cor. Sec. 19.

6-1893 William Fraser (P. 514 No. 481), Deputy County Surveyor found stone P. 500.

6-1893 William Fraser (P. 516 No. 482) found the stone P. 514.

11-8-1976 County Surveyor found the remaining 13" of the recorded stone. Set a C.I.M. over a 1/2" x 2' rod as the corner and set the stone on the South side of the C.I.M.

5-31-1988 County Surveyor found C.I.M. in good condition. Set survey marker sign on post west 0.8'. Fences E-W-N now lying on ground.

8-17-2007 County Surveyor found CIM down 0.3' in good condition.