Certificate of Location of Government Corner

ID#: 712206 **Description:** 1/4 SEC COR 21 22 71 **Date Set:** 6/21/2011 **County:** Olmsted

Section: 22 **Township:** 107N **Range:** 11W **Monument Description:** Brass plug in concrete road

Reference Ties:

The corner falls 0.1' east of centerline crack of CSAH 10 and in line with fence east.
The monument is at the surface.
Top center 2 1/2" shaft CP (top is tappered to 1 1/2") E 46.6'
This corner is located by GPS reference stations "Big Head and Todd"

Corner History:

1853 Gov't Notes: Wm. A. Jones, set 1/4 section corner post M&L 40 chs 2640'.

6-1895 W. Fraser (P.575 No.526) found stone accepted as corner in center road, left as found, no meas this survey.

4-1898 W. Fraser (P.625 No.567) found stone P.575. Used to set 21-22-27-28, meas south to S 33-34 short 32-1/2 links or 39.93-1/2 2635.71 each 1/2 mile.

10-1900 W. Fraser (P.692-8 No.615) found stone P.575 in line fence running west. Meas north 39.84 2629.44' 2-1/2 miles to 3-4-9-10 each 1/2 mile 39.84.

10-17-1974 County Surveyor dug 9' deep in E lane C.R. #10 and found a square dark hole running about 6" deep into the clay. Accepted this as the corner and drove 2"x30" pipe in the hole and set a 1/2" rod at the surface. RP's Bottle cap on S side of PP SW 67.42, bottle cap in N side corner post W 59.74, Top center 2-1/2" shaft cor post (top is tappered to 1-1/2") E 46.6.

3-7-2007 County Surveyor found 3/4" rerod down 1.0' leaning to the south and west. Will return after frost is out to finish work.

8-29-2008 County Surveyor found 3/4" rerod down 1' leaning to the south. Removed rerod and found nothing further.

6-21-2011 County survey crew set a brass plug in concrete road using previous GPS coordinates.