Certificate of Location of Government Corner

ID#: 712304 **Description:** 1/4 SEC COR 23 26 71 **Date Set:** 9/30/1974 **County:** Olmsted

Section: 23 **Township:** 107N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 2' west of centerline of CR 107 south and in centerline of CR 107 west
County Survey Disk in W side 24" Burr Oak N 109.4'
County Survey Disk in SE side PP #1090 SW 50.6'
Punch hole in top center S end 18" CMP WSW 194.43'
Punch hole in top center N end 18" CMP WNW 198.07'
SE corner 4" square TCM box NE 36.15'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes Wm. A. Jones, set 1/4 section corner post M&L 40 chs 2640. Corner in inters E-W-S Twsp roads. Farm line boundary north, corner in very high level plateau sloping L to river.

10-1896 W. Fraser (P.595 No.541 S.23-4-5-6) 5 parties corner lost, no knowledge of location or by digging. Set stone and stake as corner, corner as L. 1/16 east set stone and stake 19.95-1/4 1316.9 M&L to "C". Meas west 39.90-1/2 to M 2633.73.

9-30-1974 County Surveyor dug with backhoe and found W. Fraser's stone (5"x10") 4' deep in "T" intersection set a 5/8"x20" rod on the S side of the stone with no iron under the CIM.

8-7-2009 County Surveyor found CIM down 0.8' in good condition.

3-9-2010 County Surveyor found CIM down 0.8' in good condition.