Certificate of Location of Government Corner

ID#: 712405 **Description:** SEC COR 23 24 25 26 71 **Date Set:** 5/18/1992 **County:** Olmsted

Section: 24 **Township:** 107N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 2' north of centerline of twp road west and 6' west of centerline of twp road north
County Survey Disk in PP #1099 ENE 37.29'
County Survey Disk in W side PP #1098 S 31.21'
This corner is located by GPS measurement

Corner History:

9-1853 Gov't Notes William Jones, Deputy Surveyor North between sections 25 and 26. 80.00 chs Set corner post in mound of earth and sod. Made trench and pits and planted osage orange seed NW and SE of trench.

10-1896 William Fraser (P. 595 No. 541), County Surveyor, dug a rod square but could not find corner. Set 2' cedar stake with boulder on top and then cedar stake on top boulder.

9-28-1974 Roger Brand, County Surveyor, dug and found stake with boulder stone beneath. Placed 3/4" x 15" rod over stone and set CIM over all.

5-18-1992 County Surveyor found CIM broken from road construction, lower section fit ties closely, set 20" CIM over lower section.

11-13-2000 County Surveyor found CIM down 0.3' in good condition.

7-20-2009 County Surveyor found CIM down 0.4' in good condition.