Certificate of Location of Government Corner

ID#: 712506 **Description:** 1/4 SEC COR 25 26 71 **Date Set:** 8/3/2010 **County:** Olmsted

Section: 25 **Township:** 107N **Range:** 11W **Monument Description:** Cast Iron Cap on Telspar Pipe

Reference Ties:

This corner is located by GPS reference stations "Reisdorf A & B"
The corner is 4' west of N-S fence
Set post with sign 5' east

Corner History:

10-1853 Gov't Notes: Original B trees 14" Burr Oak S50°W 49 lks 32.34, 15" Burr Oak N63°E 196 lks 129.36. 39.00 a stream 70 lks wide course NE and ascent bluff.

10-1896 W. Fraser (P.595 No.541), corner gone, found 2 B tree stumps SW B tree blaze plain NE BT N57°E not N63°E set new stake from SW BT. Run N-S line corner 10 links west of straight line and 11-1/2 south of halfway making 39.95 (2636.7) north 39.72 (2621.52) south. South half of mile very rough land impossible for accuracy.

11-15-2000 County Surveyor visited area, found nothing. County Surveyor computed a position based on proportion of Will Fraser's 1896 measurements.

7-29-2010 County Surveyor computed a point at the Will Fraser 1896 position of stake set from witness tree stumps that fell 10 links west of line between section corners and 11 1/2 links south of the lost position. County survey crew traversed to the location which falls on a steep slope from north and west and about halfway between top of hill and riverbank. The position falls 4' west of tree to tree fence line. No monuments or bearing tree evidence was found.

8-3-2010 County survey crew set a 4' telspar pipe with cast iron cap up 0.1' at Will Fraser 1896 position