Certificate of Location of Government Corner

ID#: 712604 **Description:** 1/4 SEC COR 26 35 71 **Date Set:** 8/17/1977 **County:** Olmsted

Section: 26 **Township:** 107N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is down 0.2'
The corner falls 3' west of N-S fence and 3.5' south of fence east
Spike in E side 5" Cedar NW 56.82'
Spike in W side PP #1064 NW 12.81'
Spike in SE side wood fence post NE 4.27'
This corner is located by GPS measurement

Corner History:

10-1853 Gov't Notes William A. Jones, Deputy Surveyor West between sections 26 and 35. 39.94 chs. Set a quarter section post at average distance from whence a Burr Oak 9 in. diam. N31°W 204 lks. Made a trench. 79.88 chs. To section corner.

10-1896 William Fraser (P.595 No.541), County Surveyor, found a bearing tree with marks all plain and by the U.S. Field Notes found the remains of the stake which corresponded with the bearing tree. Set a stone with a stake by its side for the corner.

10-1902 William Fraser (Bk. B, Pg. 26) found the stone and stake set p. 595. Set stones at the 1/16th South and the Center 35.

8-17-1977 County Surveyor found a 6"x6"x16" stone flush with the ground surface with a possible stake hole beneath and with a drag tooth lying down along side. Set a C.I.M. over a ½"x2' rod as the corner and set the stone on the East side. Also, found Fraser's stones at the 1/16th South and the Center 35.

6-30-1994 County Surveyor found C.I.M. with stone beside in good condition.

8-2-2010 County survey crew found CIM in good condition.